

PRODUCT SPECIFICATIONS

61" 19oz VINYL STRUCTURE PVC Coated Polyester TI P/N: VI-19-061-100-FR-ST

Width	61 inches
Base Fabric (100% Polyester)	1000D x 1000D / 23 x 23
Weight (FS-191-5041)	19 oz / yard ²
Tensile Strength (Grab) (FS-191-5100)	455 lbs x 455 lbs
Tensile Strength (Strip) (FS-191-5102)	375 lbs x 375 lbs
Tear Strength (Tongue) (FS-191-5134)	120 lbs x 120 lbs
Adhesion Strength (FS-191-5970)	11 x 11 lbs / inch
Abrasion Resistance (FS-191-5306)	500 cycles
Hydrostatic Resistance (FS-191-5512)	At least 600 lbs / inch ²
U.V. Resistance (Weather-O-Meter)	Not excessive fading after 1000 HRS
Cold Crack Resistance (FS-191-5874)	-40° F
High Temperature Resistance (FS-191-5872)	180° F (Does not Block)
Flame Resistance	NFPA 701 Large & Small Scale - PASS
Special Treatment(s)	GLOSS Acrylic Lacquer / U.V. Inhibitors

This information is offered for your general guidance only. Above values represent typical data and are subject to slight variations. It is accurate to the best of our knowledge at the time of printing but is not intended to relieve the user from its responsibility to investigate and understand other pertinent sources of information and to comply with all laws and procedures applicable to safe handling of this material. No warranty is expressed or implied regarding the accuracy of these data.